



CT TYPE: PRIMARY WOUND BNP
 PRIMARY CURRENT: 1-100A SECONDARY OUTPUT: 1A, 5A
 SYSTEM VOLTAGE: 660VAC
 OUTER DIMENSION: 111mm HEIGHT 68mm WIDTH 43mm DEPTH

FREQUENCY: 50Hz
 STANDARD: IEC/SANS 61869-2

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTBNP-1/5AE	NA	10VA	NA
CTBNP-2.5/5AE	NA	10VA	NA
CTBNP-5/5AE	NA	10VA	NA
CTBNP-10/5AE	NA	10VA	NA
CTBNP-15/5AE	NA	10VA	NA
CTBNP-20/5AE	NA	10VA	NA
CTBNP-25/5AE	NA	10VA	NA
CTBNP-30/5AE	NA	10VA	NA
CTBNP-40/5AE	NA	10VA	NA
CTBNP-50/5AE	NA	10VA	NA
CTBNP-60/5AE	NA	10VA	NA
CTBNP-75/5AE	NA	10VA	NA
CTBNP-80/5AE	NA	10VA	NA
CTBNP-100/5AE	NA	10VA	NA

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTBNP-1/1AE	NA	10VA	NA
CTBNP-2.5/1AE	NA	10VA	NA
CTBNP-5/1AE	NA	10VA	NA
CTBNP-7.5/1AE	NA	10VA	NA
CTBNP-10/1AE	NA	10VA	NA
CTBNP-15/1AE	NA	10VA	NA
CTBNP-20/1AE	NA	10VA	NA
CTBNP-25/1AE	NA	10VA	NA
CTBNP-30/1AE	NA	10VA	NA
CTBNP-40/1AE	NA	10VA	NA
CTBNP-50/1AE	NA	10VA	NA
CTBNP-60/1AE	NA	10VA	NA
CTBNP-75/1AE	NA	10VA	NA
CTBNP-80/1AE	NA	10VA	NA
CTBNP-100/1AE	NA	10VA	NA