



CT TYPE: RING TYPE BR1
 PRIMARY CURRENT: 200-2000A SECONDARY OUTPUT: 1A, 5A
 SYSTEM VOLTAGE: 660VAC
 OUTER DIMENSION: 130mm HEIGHT 140mm WIDTH 45mm DEPTH
 STANDARD: IEC/SANS 61869-2
 INNER DIAMETER: 63mm
 BUSBAR: 60MM

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTBR1-200/5AE	1,25VA	3,75VA	5VA
CTBR1-250/5AE	3,75VA	5VA	7,5VA
CTBR1-300/5AE	3,75VA	10VA	15VA
CTBR1-350/5AE	5VA	15VA	20VA
CTBR1-400/5AE	5VA	15VA	20VA
CTBR1-500/5AE	10VA	25VA	30VA
CTBR1-600/5AE	15VA	30VA	30VA
CTBR1-700/5AE	5VA	30VA	30VA
CTBR1-800/5AE	7,5VA	30VA	30VA
CTBR1-1000/5AE	25VA	30VA	30VA
CTBR1-1200/5AE	20VA	25VA	30VA
CTBR1-1250/5AE	20VA	30VA	30VA
CTBR1-1500/5AE	25VA	30VA	30VA
CTBR1-1600/5AE	30VA	30VA	30VA
CTBR1-2000/5AE	30VA	30VA	30VA

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTBR1-200/1AE	3,75VA	5VA	7,5VA
CTBR1-250/1AE	5VA	10VA	15VA
CTBR1-300/1AE	5VA	10VA	15VA
CTBR1-400/1AE	15VA	25VA	30VA
CTBR1-500/1AE	25VA	30VA	30VA
CTBR1-600/1AE	30VA	30VA	30VA
CTBR1-700/1AE	10VA	20VA	25VA
CTBR1-800/1AE	20VA	25VA	30VA
CTBR1-1000/1AE	20VA	25VA	30VA
CTBR1-1200/1AE	25VA	30VA	30VA
CTBR1-1250/1AE	25VA	30VA	30VA
CTBR1-1500/1AE	25VA	30VA	30VA
CTBR1-1600/1AE	30VA	30VA	30VA
CTBR1-2000/1AE	10VA	15VA	20VA