



CT TYPE: RING TYPE BR2
PRIMARY CURRENT: 400-2000A SECONDARY OUTPUT: 1A, 5A
SYSTEM VOLTAGE: 660VAC
OUTER DIMENSION: 150mm HEIGHT 160mm WIDTH 30mm DEPTH
FREQUENCY: 50Hz
STANDARD: IEC/SANS 61869-2
INNER DIAMETER: 70mm
BUSBAR: 80MM

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTBR2-400/5AE	2.5VA	7.5VA	10VA
CTBR2-500/5AE	2.5VA	7.5VA	10VA
CTBR2-600/5AE	3.75VA	10VA	15VA
CTBR2-700/5AE	5VA	15VA	20VA
CTBR2-800/5AE	5VA	15VA	20VA
CTBR2-1000/5AE	15VA	30VA	30VA
CTBR2-1200/5AE	15VA	30VA	30VA
CTBR2-1250/5AE	15VA	30VA	30VA
CTBR2-1500/5AE	20VA	30VA	30VA
CTBR2-1600/5AE	30VA	30VA	30VA
CTBR2-2000/5AE	30VA	30VA	30VA
CTBR2-2500/5AE	NA	NA	NA

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTBR2-400/1AE	2.5VA	5VA	7.5VA
CTBR2-500/1AE	3.75VA	7.5VA	10VA
CTBR2-600/1AE	3.75VA	7.5VA	10VA
CTBR2-700/1AE	5VA	10VA	15VA
CTBR2-800/1AE	7.5VA	10VA	15VA
CTBR2-1000/1AE	7.5VA	10VA	15VA
CTBR2-1200/1AE	10VA	15VA	20VA
CTBR2-1250/1AE	10VA	15VA	20VA
CTBR2-1500/1AE	10VA	15VA	20VA
CTBR2-1600/1AE	15VA	20VA	25VA
CTBR2-2000/1AE	30VA	30VA	30VA
CTBR2-2500/1AE	NA	NA	NA