



CT TYPE: RING TYPE BR3	FREQUENCY: 50Hz
PRIMARY CURRENT: 400-3200A SECONDARY OUTPUT: 1A, 5A	STANDARD: IEC/SANS 61869-2
SYSTEM VOLTAGE: 660VAC	INNER DIAMETER: 110mm
OUTER DIMENSION: 180mm HEIGHT 204mm WIDTH 45mm DEPTH	BUSBAR: 100MM

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTBR3-400/5AE	5VA	10VA	15VA
CTBR3-500/5AE	5VA	15VA	20VA
CTBR3-600/5AE	7.5VA	25VA	30VA
CTBR3-700/5AE	10VA	30VA	30VA
CTBR3-800/5AE	15VA	30VA	30VA
CTBR3-1000/5AE	20VA	30VA	30VA
CTBR3-1200/5AE	30VA	30VA	30VA
CTBR3-1250/5AE	7.5VA	30VA	30VA
CTBR3-1500/5AE	15VA	30VA	30VA
CTBR3-1600/5AE	30VA	30VA	30VA
CTBR3-2000/5AE	30VA	30VA	30VA
CTBR3-2500/5AE	30VA	30VA	30VA
CTBR3-3000/5AE	30VA	30VA	30VA
CTBR3-3200/5AE	30VA	30VA	30VA

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTBR3-400/1AE	NA	2.5VA	3.75VA
CTBR3-500/1AE	NA	3.75VA	5VA
CTBR3-600/1AE	2.5VA	5VA	7.5VA
CTBR3-700/1AE	2.5VA	5VA	7.5VA
CTBR3-800/1AE	3.75VA	10VA	15VA
CTBR3-1000/1AE	3.75VA	25VA	30VA
CTBR3-1200/1AE	5VA	30VA	30VA
CTBR3-1250/1AE	7.5VA	30VA	30VA
CTBR3-1500/1AE	25VA	30VA	30VA
CTBR3-1600/1AE	25VA	30VA	30VA
CTBR3-2000/1AE	30VA	30VA	30VA
CTBR3-2500/1AE	30VA	30VA	30VA
CTBR3-3000/1AE	30VA	30VA	30VA
CTBR3-3200/1AE	30VA	30VA	30VA