



CT TYPE: RING TYPE MN1			
PRIMARY CURRENT: 50 - 400A SECONDARY OUTPUT: 1A, 5A			
SYSTEM VOLTAGE: 660VAC			
OUTER DIMENSION: 87mm HEIGHT 64mm WIDTH 42mm DEPTH			
FREQUENCY: 50Hz			
STANDARD: IEC/SANS 61869-2			
INNER DIAMETER: 32mm			
Product code		Available Class and burden	
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTMN1-50/5AE	NA	1,25VA	2,5VA
CTMN1-60/5AE	NA	1,25VA	2,5VA
CTMN1-75/5AE	NA	1,25VA	2,5VA
CTMN1-80/5AE	NA	1,25VA	2,5VA
CTMN1-100/5AE	NA	2,5VA	3,75VA
CTMN1-120/5AE	NA	2,5VA	3,75VA
CTMN1-125/5AE	NA	2,5VA	3,75VA
CTMN1-150/5AE	NA	3,75VA	5VA
CTMN1-160/5AE	1,25VA	3,75VA	5VA
CTMN1-175/5AE	1,25VA	3,75VA	5VA
CTMN1-200/5AE	1,25VA	5VA	7,5VA

CTMN1-250/5AE	3,75VA	5VA	7,5VA
CTMN1-300/5AE	3,75VA	10VA	15VA
CTMN1-400/5AE	10VA	25VA	30VA

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTMN1-50/1AE	NA	NA	1,25VA
CTMN1-60/1AE	NA	NA	1,25VA
CTMN1-75/1AE	NA	1,25VA	2,5VA
CTMN1-80/1AE	NA	1,25VA	2,5VA
CTMN1-100/1AE	NA	2,5VA	3,75VA
CTMN1-120/1AE	NA	2,5VA	3,75VA
CTMN1-125/1AE	1,25VA	3,75VA	5VA
CTMN1-150/1AE	2,5VA	5VA	7,5VA
CTMN1-160/1AE	2,5VA	5VA	7,5VA
CTMN1-175/1AE	2,5VA	5VA	7,5VA
CTMN1-200/1AE	3,75VA	7,5VA	10VA
CTMN1-250/1AE	5VA	10VA	15VA
CTMN1-300/1AE	10VA	10VA	15VA
CTMN1-400/1AE	10VA	15VA	20VA

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTMN1T-4-20MAE	NA	NA	NA
CTMN2T-4-20MAE	NA	NA	NA