



CT TYPE: RING TYPE MN2	FREQUENCY: 50Hz
PRIMARY CURRENT: 50 - 800A SECONDARY OUTPUT: 1A, 5A	STANDARD: IEC/SANS 61869-2
SYSTEM VOLTAGE: 660VAC	INNER DIAMETER: 38mm
OUTER DIMENSION: 99mm HEIGHT 75mm WIDTH 42mm DEPTH	BUSBAR: 40MM

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTMN1-125/1AE	NA	NA	1,25VA
CTMN1-160/1AE	NA	1,25VA	2,5VA
CTMN1-250/5AE	NA	1,25VA	2,5VA
CTMN1-300/5AE	NA	1,25VA	2,5VA
CTBR3-2500/5AE	NA	2,5VA	3,75VA
CTBR3-3000/5AE	NA	2,5VA	3,75VA
CTBR3-3200/5AE	NA	3,75VA	5VA
CTBR3-400/5AE	1,25VA	3,75VA	5VA
CTBR3-500/5AE	1,25VA	3,75VA	5VA
CTBR3-600/5AE	1,25VA	3,75VA	5VA
CTBR3-700/1AE	2,5VA	5VA	7,5VA
CTBR3-800/1AE	3,75VA	10VA	10VA
CTMN1-100/1AE	5VA	15VA	15VA
CTMN1-120/1AE	10VA	25VA	30VA
CTMN1-150/1AE	20VA	30VA	30VA
CTMN1-175/1AE	30VA	30VA	30VA
CTMN1-200/5AE	30VA	30VA	30VA
CTMN1-400/5AE	5VA	10VA	15VA

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTMN1-120/5AE	NA	NA	1,25VA
CTMN1-150/5AE	NA	NA	1,25VA
CTMN1-250/1AE	NA	1,25VA	2,5VA
CTMN1-300/1AE	NA	1,25VA	2,5VA
CTBR3-2500/1AE	NA	2,5VA	3,75VA
CTBR3-3000/1AE	NA	3,75VA	5VA
CTBR3-3200/1AE	NA	3,75VA	5VA
CTBR3-400/1AE	1,25VA	5VA	7,5VA
CTBR3-500/1AE	2,5VA	5VA	7,5VA
CTBR3-600/1AE	2,5VA	5VA	7,5VA
#REF!	5VA	10VA	15VA
CTBR3-700/5AE	7,5VA	15VA	20VA
CTBR3-800/5AE	10VA	15VA	20VA
CTMN1-100/5AE	15VA	25VA	30VA
CTMN1-125/5AE	3,75VA	7,5VA	10VA
CTMN1-160/5AE	3,75VA	10VA	15VA
CTMN1-200/1AE	7,5VA	10VA	15VA
CTMN1-400/1AE	10VA	10VA	15VA