



CT TYPE: RING TYPE MN2
 PRIMARY CURRENT: 50 - 800A SECONDARY OUTPUT: 1A, 5A
 SYSTEM VOLTAGE: 660VAC
 OUTER DIMENSION: 99mm HEIGHT 75mm WIDTH 42mm DEPTH
 FREQUENCY: 50Hz
 STANDARD: IEC/SANS 61869-2
 INNER DIAMETER: 38mm
 BUSBAR: 40MM

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTMN2-50/5AE	NA	NA	1,25VA
CTMN2-60/5AE	NA	1,25VA	2,5VA
CTMN2-75/5AE	NA	1,25VA	2,5VA
CTMN2-80/5AE	NA	1,25VA	2,5VA
CTMN2-100/5AE	NA	2,5VA	3,75VA
CTMN2-120/5AE	NA	2,5VA	3,75VA
CTMN2-125/5AE	NA	3,75VA	5VA
CTMN2-150/5AE	1,25VA	3,75VA	5VA
CTMN2-160/5AE	1,25VA	3,75VA	5VA

CTMN2-175/5AE	1,25VA	3,75VA	5VA
CTMN2-200/5AE	2,5VA	5VA	7,5VA
CTMN2-250/5AE	3,75VA	10VA	10VA
CTMN2-300/5AE	5VA	15VA	15VA
CTMN2-350/5AE	5VA	10VA	15VA
CTMN2-400/5AE	10VA	25VA	30VA
CTMN2-500/5AE	20VA	30VA	30VA
CTMN2-600/5AE	30VA	30VA	30VA
CTMN2-700/5AE	30VA	30VA	30VA
CTMN2-800/5AE	5VA	10VA	15VA

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTMN2-50/1AE	NA	NA	1,25VA
CTMN2-60/1AE	NA	NA	1,25VA
CTMN2-75/1AE	NA	1,25VA	2,5VA
CTMN2-80/1AE	NA	1,25VA	2,5VA
CTMN2-100/1AE	NA	2,5VA	3,75VA
CTMN2-120/1AE	NA	3,75VA	5VA
CTMN2-125/1AE	NA	3,75VA	5VA
CTMN2-150/1AE	1,25VA	5VA	7,5VA
CTMN2-160/1AE	2,5VA	5VA	7,5VA
CTMN2-175/1AE	2,5VA	5VA	7,5VA
CTMN2-200/1AE	5VA	10VA	15VA
CTMN2-250/1AE	7,5VA	15VA	20VA
CTMN2-300/1AE	10VA	15VA	20VA
CTMN2-350/1AE	5VA	10VA	15VA
CTMN2-400/1AE	15VA	25VA	30VA
CTMN2-500/1AE	3,75VA	7,5VA	10VA
CTMN2-600/1AE	3,75VA	10VA	15VA
CTMN2-700/1AE	7,5VA	10VA	15VA
CTMN2-800/1AE	10VA	10VA	15VA