



CT TYPE: PRIMARY WOUND SNP
 PRIMARY CURRENT: 1-50A SECONDARY OUTPUT: 1A, 5A
 SYSTEM VOLTAGE: 660VAC
 OUTER DIMENSION: 95mm HEIGHT 52mm WIDTH 42mm DEPTH

FREQUENCY: 50Hz
 STANDARD: IEC/SANS 61869-2

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTSnp-1/5AE		2,5VA	
CTSnp-2/5AE		2,5VA	
CTSnp-2.5/5AE		2,5VA	
CTSnp-5/5AE		2,5VA	
CTSnp-7.5/5AE		2,5VA	
CTSnp-10/5AE		2,5VA	
CTSnp-15/5AE		2,5VA	
CTSnp-20/5AE		2,5VA	
CTSnp-25/5AE		2,5VA	
CTSnp-30/5AE		2,5VA	
CTSnp-40/5AE		2,5VA	
CTSnp-50/5AE		2,5VA	

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTSnp-1/1AE		2,5VA	
CTSnp-2/1AE		2,5VA	
CTSnp-2.5/1AE		2,5VA	
CTSnp-5/1AE		2,5VA	
CTSnp-7.5/1AE		2,5VA	
CTSnp-10/1AE		2,5VA	
CTSnp-15/1AE		2,5VA	
CTSnp-20/1AE		2,5VA	
CTSnp-25/1AE		2,5VA	
CTSnp-30/1AE		2,5VA	
CTSnp-40/1AE		2,5VA	
CTSnp-50/1AE		2,5VA	