



CT TYPE: PRIMARY WOUND SNP
PRIMARY CURRENT: 1-50A SECONDARY OUTPUT: 1A, 5A
SYSTEM VOLTAGE: 660VAC
OUTER DIMENSION: 95mm HEIGHT 52mm WIDTH 42mm DEPTH
FREQUENCY: 50Hz
STANDARD: IEC/SANS 61869-2

Product code	Available Class and burden		
	Class 0,5(VA)	CLASS 1(VA)	CLASS 3(VA)
CTSNP-1/5AE		2,5VA	
CTSNP-2/5AE		2,5VA	
CTSNP-2.5/5AE		2,5VA	
CTSNP-5/5AE		2,5VA	
CTSNP-7.5/5AE		2,5VA	
CTSNP-10/5AE		2,5VA	
CTSNP-15/5AE		2,5VA	
CTSNP-20/5AE		2,5VA	
CTSNP-25/5AE		2,5VA	
CTSNP-30/5AE		2,5VA	
CTSNP-40/5AE		2,5VA	
CTSNP-50/5AE		2,5VA	

Product code	Available Class	and burden	CLASS 3(VA)
	Class 0,5(VA)	CLASS 1(VA)	
CTSNP-1/1AE		2,5VA	
CTSNP-2/1AE		2,5VA	
CTSNP-2.5/1AE		2,5VA	
CTSNP-5/1AE		2,5VA	
CTSNP-7.5/1AE		2,5VA	
CTSNP-10/1AE		2,5VA	
CTSNP-15/1AE		2,5VA	
CTSNP-20/1AE		2,5VA	
CTSNP-25/1AE		2,5VA	
CTSNP-30/1AE		2,5VA	
CTSNP-40/1AE		2,5VA	
CTSNP-50/1AE		2,5VA	