



Transducers

CODE	PRODUCT DESCRIPTION	
MT416-132V4-UI	MT416	Input 132V, Output 4-20mA, Auxiliary Universal(AC (40–276V AC) DC (24–300V DC))
MT418-6A4-UI	MT418	Input (0-6A), Output (4-20mA), Auxiliary Power :Universal(AC (40–276V AC) DC (24–300V DC))
MT440-1X232UI	MT440	Output:1, xCom:RS232, Auxiliary Power :Universal(AC (40–276V AC) DC (24–300V DC))
MT440-1X485UI	MT440	Output:1, xCom:RS485, Auxiliary Power :Universal(AC (40–276V AC) DC (24–300V DC))
MT440-2X232UI	MT440	Output:2, xCom:RS232, Auxiliary Power :Universal(AC (40–276V AC) DC (24–300V DC))
MT440-2X485UI	MT440	Output:2, xCom:RS485, Auxiliary Power :Universal(AC (40–276V AC) DC (24–300V DC))
MT440-3X232UI	MT440	Output:3, xCom:RS232, Auxiliary Power :Universal(AC (40–276V AC) DC (24–300V DC))
MT440-3X485UI	MT440	Output:3, xCom:RS485, Auxiliary Power :Universal(AC (40–276V AC) DC (24–300V DC))
MT440-4X232UI	MT440	Output:4, xCom:R232, Auxiliary Power :Universal(AC (40–276V AC) DC (24–300V DC))
MT440-4X485UI	MT440	Output:4, xCom:RS485, Auxiliary Power :Universal(AC (40–276V AC) DC (24–300V DC))
MT440-4XF232UI	MT440	Out:4x, FastCom, RS232, Auxiliary Power :Universal(AC (40–276V AC) DC (24–300V DC))